Laser Induced Aluminum Surface Breakdown Model

Progress Report

Order Number: H-33325D

Prepared for

National Aeronautics and Space Administration George C. Marshall Space Flight Center Marshall Space Flight Center, AL 35812

by

Y. S. Chen J. Liu S. Zhang

Engineering Sciences, Inc. 1900 Golf Road, Suite D Huntsville, AL 35802 (256) 883-6233

September 15, 2001

Laser Induced Aluminum Surface Breakdown Model

OBJECTIVES

dynamics, involve complex fluid propulsion systems Laser powered thermodynamics and radiative transfer processes. Based on an unstructured grid, pressure-based computational aerothermodynamics platform, several submodels describing such underlying physics as laser ray tracing and focusing, thermal non-equilibrium, plasma radiation and air spark ignition have been developed. This proposed work shall extend the numerical platform and existing sub-models to include the aluminum wall surface Inverse Bremsstrahlung (IB) effect from which surface ablation and free-electron generation can be initiated without relying on the air spark ignition sub-model. The following tasks will be performed to accomplish the research objectives.

TASKS PERFORMED IN THIS REPORTING PERIOD

In this reporting period, mechanisms for initializing the aluminum surface ablation and ionization due to focused laser energy is formulated and planned for computer coding implementation. At the start of the laser pulse, the beams are focused at a small area on the aluminum surface of the test vehicle. Part of the energy is absorbed by the material and causes to overcome the bounding energy of the molecules. This process is accounted for through stopping power as described by Harada [1-4]. In the present model, the energy absorbed, as output from the radiation model, is used to calculate the evaporation rates of the aluminum material from the surface. The ionization of the ablated material is then initiated by using the Saha's equation under the thermal and chemical equilibrium assumption [4].

The UNIC-UNS pulsed laser supported propulsion numerical model is further modified to enable parallel computing for efficient computations, especially for three-dimensional models. The ray tracing radiative heat transfer model, laser ray inlet boundary conditions, laser reflection conditions, thrust force time integration and performance data integration are implemented to work in parallel computing environment. Full 3D ray tracing radiation model is also implemented in this task. This model has been tested successfully using 2D and 3D laser lightcraft model-A configuration and test conditions.

A new treatment for modeling the laser absorption when the local electron number density reaches the resonant critical value has been developed to remove the difficulty of calculating short pulse width conditions due to very high laser power. Previously, a resonant absorption constant is assumed as soon as the local electron number density reaches the critical value. This creates a step jump in energy input to the local computational cells and causes the instability of the numerical model. To circumvent this problem, a smooth variation in the energy absorption is assumed before the laser rays reach the plasma resonance front. This smooth absorption function is constructed based on the electron number density. Preliminary calculation using this treatment showed increased integrated thrust coupling coefficients for normal pulse width cases. Test for a short pulse-width case (with 1 microsecond pulse width) has shown good stability of the computational model. Fine-tuning of this treatment is necessary to anchor the modeling constants for its applicability over a selected range of pulse widths and power levels.

References

- Harada, Nob., Kagihiro, M., Shinkai, H., Jiang, W. and Yatsui, K., "Flyer Acceleration by Ablation Plasma Using an Intense Pulsed Ion Beam," AIAA 99-3485, 30th Plasmadynamics and Lasers Conference, 28 June – 1 July, 1999, Norfolk, VA.
- Harada, Nob., Yazawa, M., Kashine, K., Jiang, W. and Yatsui, K., "Numerical Simulation of Foil Acceleration by Intense Pulsed Ion Beam," AIAA 2000-2272, 31st AIAA Plasmadynamics and Lasers Conference, 19-22 June, 2000, Denver, CO.
- 3. Harada, Nob., "Acceleration of Multi-Layer Foil by Intense Pulsed Ion Beam," AIAA 2001-3005, 32nd AIAA Plasmadynamics and Lasers Conference, 11-14 June, 2001, Anaheim, CA.
- 4. Harada, Nob., (Private Communication), September, 2001.

TASKS TO BE PERFORMED IN THE NEXT PERIOD

- 1. Perform calculation of aluminum surface ablation and ionization with laser energy input.
- 2. Continue computation of short pulse width cases and to fine-tune the resonant laser absorption model.

CONTRACT PERFORMANCE AND FUNDING

30% of the proposed technical effort has been accomplished with 30% of the funding billed. No technical problem of the current model development has been encountered.



Engineering Sciences, Inc. 1900 Golf Road, Suite D Huntsville, Alabama 35802

(256) 883-6233 / FAX:(256) 883-6267

September 15, 2001

To:

Center for AeroSpace Information (CASI)

Attn: Document Processing Section

Parkway Center 7121 Standard Drive

Hanover, MD 21076-1320

From: Yen-Sen Chen, Engineering Sciences, Inc., Huntsville, Alabama

Subject:

Interim Technical Report for the Order No. H-33325D

-- LASER INDUCED ALUMINUM SURFACE BREAKDOWN MODEL

Sincerely,

ESI

Yen-Sen Chen

President

Distribution List	No. Copies
PS52H / Kimberly Day	1
CD30 / New Technology Representative	1
AD30 / Information Services Dept.	1
TD64 / Ten-See Wang	1
Center for AeroSpace Information (CASI)	1

REPORT DOCUMENTATION PAGE		Form Approved OMB No. 0704-0188		
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing date sources, gathering and multipartities the date needed, and computing and reviewing the collection of information. Sand comments regarding this burden estimate or any other sepect of this collection of information, including suggestions for reducing this burden, to Weshington Headers Services, Directions for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arington, Ve 22202-4302, and to the Office of Management and Budget, Paperson's Reduction Project (0704-0185), Whethington, DC 28603.				
I. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE Sept. 15, 2001	3. REPORT TYPE AND D. Interim; 6/5		
4. TITLE AND SUBTITLE Laser Induced	Aluminum Surface Breakdown		i. FUNDING NUMBERS	
6. AUTHOR(S) Yen-Sen	Chen, Jiwen Liu and Sijun Zha	ng	H-33325D	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Engineering Sciences, Inc. 1900 Golf Road, Suite D, Huntsville, AL 35802		B. PERFORMING ORGANIZATON REPORT NUMBERS		
0	C. Marshall Space Flight Center Space Flight Center, AL 3581	r	10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Ten-See Wang / Technical Monitor				
12a. DISTRIBUTION/AVAILABILITY	STATEMENT		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)				
Laser powered propulsion systems involve complex fluid dynamics, thermodynamics and radiative transfer processes. Based on an unstructured grid, pressure-based computational aerothermodynamics platform, several sub-models describing such underlying physics as				
laser ray tracing and focusing, thermal non-equilibrium, plasma radiation and air spark				
ignition have been developed. This proposed work shall extend the numerical platform and existing sub-models to include the aluminum wall surface Inverse Bremsstrahlung (IB) effect				
from which surface ablation and free-electron generation can be initiated without relying on				
the air spark ignition sub-model. The following tasks will be performed to accomplish the				
research objectives.				
			•	
14. SUBJECT TERMS	11	Indication Madellin	15. NUMBER OF PAGES	
Laser Propulsion Analysis, Aluminum Surface Breakdown, Ionization Modeling		16. PRICE CODE		
17. SECURITY CLASSIFICATION	8. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT	

Unclassified

Unlimited

Unclassified

Unclassified